

Model: Amhara Multicolor
 Size: 10X20 cm (3.9x7.9 in)
 Thickness: 7.5mm
 Material type: Red Body



TECHNICAL DATA

| | | |
|--|--|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, orthogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group BIII annex L | UNE EN ISO 10545 Part 2 |
| Water absorption | E > 10% | UNE EN ISO 10545 Part 3 |
| Flexion resistance (N/mm.2) and breaking strength (N) | > 15 > 600 | UNE EN ISO 10545 Part 4 |
| Lineal thermic dilatation | < 7*10 ⁻⁶ /°C | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | Stands the test | UNE EN ISO 10545 Part 9 |
| Expansion due to moisture | < 0.6% | UNE EN ISO 10545 Part 10 |
| Cracking resistance | Stands the test | UNE EN ISO 10545 Part 11 |

CHEMICAL RESISTANCE

| | | |
|-------------------------------------|-------------------|--------------------------|
| Domestic cleaning products | Class GA | UNE EN ISO 10545 Part 13 |
| Swimming pool salt | Class GA | |
| Acids and bases (low concentration) | Minimum Class GLB | UNE EN ISO 10545 Part 14 |
| Stains resistance | Minimum Class 4 | |

CE MARKING



CE Declaration of performance:

Nº 003VV2013