

Model: Vodevil Humo
 Size: 20X20 cm (7.9x7.9 in)
 Thickness: 8mm
 Material type: Porcelain

TECHNICAL DATA

| | | |
|--|---|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, orthogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 | UNE EN ISO 10545 Part 2 |
| Water absorption | E < 0.5% | UNE EN ISO 10545 Part 3 |
| Flexion resistance (N/mm.2) y and breaking strength (N) | > 35 > 1300 | UNE EN ISO 10545 Part 4 |
| Resistance to surface abrasion (Glazed tiles) | 3 | UNE EN ISO 10545 Part 7 |
| Lineal thermic dilatation | < 9*10 ⁻⁶ /°C | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | Stands the test | UNE EN ISO 10545 Part 9 |
| Cracking resistance | Stands the test | UNE EN ISO 10545 Part 11 |
| Frost resistance | Stands the test | UNE EN ISO 10545 Part 12 |
| Slip resistance | Class 1 | UNE ENV 12633:2003 |

CHEMICAL RESISTANCE

| | | |
|-------------------------------------|-------------------|--------------------------|
| Domestic cleaning products | Class GA | |
| Swimming pool salt | Class GA | UNE EN ISO 10545 Part 13 |
| Acids and bases (low concentration) | Minimum Class GLB | |
| Stains resistance | Minimum Class 4 | UNE EN ISO 10545 Part 14 |

CE MARKING



CE Declaration of performance:

Nº 001VV2013