


VIVES

Jujol Grafito 20x20 cm (7.9x7.9 in)



Model: Jujol Grafito
 Size: 20x20 cm (7.9x7.9 in)
 Thickness: 8mm
 Material type: Gres

TECHNICAL DATA

| | | |
|---|---|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, ortogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group Blb annex H | |
| Water absorption | 0.5% < E < 3% | UNE EN ISO 10545 Part 3 |
| Flexion resistance (N/mm.2) y and breaking strength (N) | > 30Nw/mm ² > 1100Nw | UNE EN ISO 10545 Part 4 |
| Resistance to surface abrasion | 3 | UNE EN ISO 10545 Part 7 |
| Lineal thermic dilatation | < 7*10 -6 /°C | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | Stands the test | UNE EN ISO 10545 Part 9 |
| Expansion due to moisture | < 0.6% | UNE EN ISO 10545 Part 10 |
| Cracking resistance | Stands the test | UNE EN ISO 10545 Part 11 |
| Slip resistance | Class 1 | UNE 41901 EX |

CHEMICAL RESISTANCE

| | | |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products | Class A | UNE EN ISO 10545 Part 13 |
| Swimming pool salt | Class A | |
| Acids and bases (low concentration) | Minimum Class LB | |
| Stains resistance | Minimum Class 4 | UNE EN ISO 10545 Part 14 |

CE MARKING



CE Declaration of performance:
 N° 002VV2019