

**VIVES****Central 31,6x31,6 cm (12.4x12.4 in)**

Model: Central

Size: 31,6x31,6 cm (12.4x12.4 in)

Thickness: 9mm

Material type: Gres

**TECHNICAL DATA**

|   |   |                          |
|---|---|--------------------------|
| Manufacture process   | Single-firing   | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, ortogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group Blb annex H | UNE EN ISO 10545 Part 2  |
| Water absorption  | 0.5% < E < 3%   | UNE EN ISO 10545 Part 3  |
| Flexion resistance (N/mm.2) and breaking strength (N)               | > 30Nw/mm <sup>2</sup><br>> 1100Nw  | UNE EN ISO 10545 Part 4  |
| Resistance to surface abrasion                                      | 4   | UNE EN ISO 10545 Part 7  |
| Lineal thermic dilatation   | < 7*10 -6 /°C   | UNE EN ISO 10545 Part 8  |
| Thermic impact resistance   | Stands the test   | UNE EN ISO 10545 Part 9  |
| Expansion due to moisture   | < 0.6%  | UNE EN ISO 10545 Part 10 |
| Cracking resistance   | Stands the test   | UNE EN ISO 10545 Part 11 |
| Slip resistance   | Class 1   | UNE 41901 EX             |

**CHEMICAL RESISTANCE**

|                                     |                  |                          |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products          | Class A          | UNE EN ISO 10545 Part 13 |
| Swimming pool salt                  | Class A          |                          |
| Acids and bases (low concentration) | Minimum Class LB |                          |
| Stains resistance                   | Minimum Class 4  | UNE EN ISO 10545 Part 14 |

**CE MARKING**

CE Declaration of performance:

Nº 002VV2019

IMPORTANT: before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the material has been fixed. A minimum joint of 1 to 2 mm is required.  
Document with commercial information and cannot be used either judicially or administratively without the express permission of VIVES Azulejos y Gres S.A.  
The color of the tile of this data sheet is for guidance only and may differ from the actual tile color.

VIVES Azulejos y Gres, S.A. Ctra. Castellón Km. 23 · Apdo. correos, 14 · 12110 Alcora ( Castellón - Spain ) · Tel.: (+34) 964 36 07 25 · info@vivesceramica.com