



Model: Zante Nieve

Size: 12'5X12'5 cm (4.9x4.9 in)

Thickness: 8mm

Material type: White Body

TECHNICAL DATA

| | | |
|--|--|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, orthogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group BIII annex L | UNE EN ISO 10545 Part 2 |
| Water absorption | $E > 10\%$ | UNE EN ISO 10545 Part 3 |
| Flexion resistance (N/mm.2) and breaking strength (N) | $> 15\text{Nw/mm}^2$ $> 600\text{Nw}$ | UNE EN ISO 10545 Part 4 |
| Lineal thermic dilatation | $< 7 \cdot 10^{-6} / ^\circ\text{C}$ | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | Stands the test | UNE EN ISO 10545 Part 9 |
| Expansion due to moisture | $< 0.6\%$ | UNE EN ISO 10545 Part 10 |
| Cracking resistance | Stands the test | UNE EN ISO 10545 Part 11 |

CHEMICAL RESISTANCE

| | | |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products | Class A | |
| Swimming pool salt | Class A | UNE EN ISO 10545 Part 13 |
| Acids and bases (low concentration) | Minimum Class LB | |
| Stains resistance | Minimum Class 4 | UNE EN ISO 10545 Part 14 |

CE MARKING



CE Declaration of performance:

Nº 003VV2013