


**VIVES**

# Mosaico Gea AB|C Mostaza 30x30 cm (11.8x11.8 in)



Model: Mosaico Gea AB|C Mostaza

Size: 30x30 cm (11.8x11.8 in)

Thickness: 9mm

Material type: Coloured Body Porcelain

## TECHNICAL DATA

|   |   |                          |
|---|---|--------------------------|
| Manufacture process   | Single-firing   | Dry pressed ceramic tile |
| Length, width, thickness, side straightness, ortogonality, flatness | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group Bla annex G |                          |
| Water absorption  | $E < 0.5\%$   | UNE EN ISO 10545 Part 3  |
| Flexion resistance (N/mm.2) and breaking strength (N)               | $> 35Nw/mm^2$<br>$> 1300Nw$   | UNE EN ISO 10545 Part 4  |
| Lineal thermic dilatation   | $< 9*10^{-6} / ^\circ C$  | UNE EN ISO 10545 Part 8  |
| Thermic impact resistance   | Stands the test   | UNE EN ISO 10545 Part 9  |
| Cracking resistance   | Stands the test   | UNE EN ISO 10545 Part 11 |
| Frost resistance  | Stands the test   | UNE EN ISO 10545 Part 12 |
| Slip resistance   | Class 2   | UNE 41901 EX             |
|   | R10   | DIN 51130                |

## CHEMICAL RESISTANCE

|                                     |                  |                          |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products          | Class A          | UNE EN ISO 10545 Part 13 |
| Swimming pool salt                  | Class A          |                          |
| Acids and bases (low concentration) | Minimum Class LB |                          |
| Stains resistance                   | Minimum Class 4  | UNE EN ISO 10545 Part 14 |

## ANTIBACTERIAL | CERAMICS

**AB|C**  
ANTIBACTERIAL | CERAMICS

Test for antibacterial activity and efficacy - 99,9%

Standard JIS Z 2801:2010 (ISO 22196)

## CE MARKING



CE Declaration of performance:

Nº 001VV2019

IMPORTANT: before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the material has been fixed. A minimum joint of 1 to 2 mm is required.  
Document with commercial information and cannot be used either judicially or administratively without the express permission of VIVES Azulejos y Gres S.A.  
The color of the tile of this data sheet is for guidance only and may differ from the actual tile color.

VIVES Azulejos y Gres, S.A. Ctra. Castellón Km. 23 · Apdo. correos, 14 · 12110 Alcora ( Castellón - Spain ) · Tel.: (+34) 964 36 07 25 · info@vivesceramica.com