



Model: Medea Gris  
 Size: 60X60 cm (23.6x23.6 in)  
 Thickness: 10mm  
 Material type: Porcelain Clay

## TECHNICAL DATA

Manufacture process	Single-firing	Dry pressed ceramic tile
Length, width, thickness, side straightness, orthogonality, flatness	Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B1b annex H	UNE EN ISO 10545 Part 2
Water absorption	$0.5\% < E < 3\%$	UNE EN ISO 10545 Part 3
Flexion resistance (N/mm.2) and breaking strength (N)	$> 30Nw/mm^2$ $> 1100Nw$	UNE EN ISO 10545 Part 4
Resistance to surface abrasion	3	UNE EN ISO 10545 Part 7
Lineal thermic dilatation	$< 7 \cdot 10^{-6} / ^\circ C$	UNE EN ISO 10545 Part 8
Thermic impact resistance	Stands the test	UNE EN ISO 10545 Part 9
Expansion due to moisture	$< 0.6\%$	UNE EN ISO 10545 Part 10
Cracking resistance	Stands the test	UNE EN ISO 10545 Part 11

## CHEMICAL RESISTANCE

Domestic cleaning products	Class A	UNE EN ISO 10545 Part 13
Swimming pool salt	Class A	
Acids and bases (low concentration)	Minimum Class LB	UNE EN ISO 10545 Part 14
Stains resistance	Minimum Class 4	

## CE MARKING



CE Declaration of performance:

Nº 001VV2013