


VIVES

Osaka Blanco 20x20 cm (7.9x7.9 in)



Model: Osaka Blanco

Size: 20x20 cm (7.9x7.9 in)

Thickness: 8mm

Material type: Porcelain

TECHNICAL DATA

Manufacture process	Single-firing	Dry pressed ceramic tile
Length, width, thickness, side straightness, ortogonality, flatness	Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group Bla annex G	UNE EN ISO 10545 Part 2
Water absorption	$E < 0.5\%$	UNE EN ISO 10545 Part 3
Flexion resistance (N/mm.2) and breaking strength (N)	$> 35Nw/mm^2$ $> 1300Nw$	UNE EN ISO 10545 Part 4
Resistance to surface abrasion	3	UNE EN ISO 10545 Part 7
Lineal thermic dilatation	$< 9 \cdot 10^{-6} / ^\circ C$	UNE EN ISO 10545 Part 8
Thermic impact resistance	Stands the test	UNE EN ISO 10545 Part 9
Cracking resistance	Stands the test	UNE EN ISO 10545 Part 11
Frost resistance	Stands the test	UNE EN ISO 10545 Part 12
Slip resistance	Class 1	UNE 41901 EX

CHEMICAL RESISTANCE

Domestic cleaning products	Class A	UNE EN ISO 10545 Part 13
Swimming pool salt	Class A	
Acids and bases (low concentration)	Minimum Class LB	
Stains resistance	Minimum Class 4	UNE EN ISO 10545 Part 14

CE MARKING



CE Declaration of performance:
Nº 001VV2019